Surface Acoustic Wave Saw Resonators 389.925MHz To 390.075MHz

Basic Information

Place of Origin: CHINA
Brand Name: ZR Hi-Tech
Model Number: LT-SR-390-307

Minimum Order Quantity:

Packaging Details: carton packing
Delivery Time: 4 weeks
Payment Terms: T/T





Product Specification

• Highlight: saw resonator crystal,

390.075MHz saw resonator, 389.925MHz saw resonator

Product Description

LT-SR-390-307 LT-SR Series SAW Resonators with Frequency Range 389.925MHz to 390.075MHz 389.925MHz to 390.075MHz LT-SR Series SAW Resonator

Quick Detail:

· Aluminum Housing

· -40°C~+85°C Operating Temperature

· SMD Package · DC Voltage: 10V

RF Power Dissipation: 0dBm CE, RoHS, REACH Compliant

· 1 Year Warranty

Description:


The LT-SR-390-3070 from ZR is a SAW Resonator with Frequency 389.925MHz to 390.075 MHz, Centre Frequency 390 MHz, Insertion Loss 1.5 to 2.2 dB, Quality Factor Loaded 13900. Tags: Surface Mount, SAW Resonator. More details for LT-SR-390-3070 can be seen below.

Specifications:

Electrical / Optical Characteristics (Ta=25°C±3°C)


Part Number : LT-SR-390-3070						
Item		Unites	Min.	Тур.	Max.	
Center Frequency		MHz	389.925	390.000	390.075	
Insertion Loss		dB		1.5	2.2	
Quality Factor Unload Q				13900		
50Ω Loaded Q				1500		
Temperature Stability	Turnover Temperature	°C	10	25	40	
	Freq.temp.Coefficient	ppm/°C2		0.037		
Frequency Aging		ppm/yr		≤±10		
DC. Insulation Resistance		ΜΩ	1.0			
RF Equivalent RLC Model	Motional Resistance R1	Ω		20	26	
	Motional Inductance L1	μН		110.52		
	Motional Capacitance C1	fF		1.51		
Transducer Static Capacitance		pF		1.70		
Note: for custom specs, please contact us directly.						

Outline Drawing (Unit: mm):



Pin	Configuration
1	Input
3	Output
2	Case Ground

Typical Frequency Response



₹ZRHITECH Sichuan ZR Hi-Tech Ltd.

13541202623

info@zrhitech.com

No.1411, Zhuye Building, 100 Xingping Road, Jinniu District, Chengdu, Sichuan Province, CHINA