# 0.02 To 3 GHz SP6T Absorptive PIN Diode Switch

# **Basic Information**

Place of Origin: CHINABrand Name: ZR Hi-Tech

Model Number: LT-SW6TA-20M030S

Minimum Order Quantity:

Packaging Details: carton packing
Delivery Time: 4 weeks
Payment Terms: T/T



# **Product Specification**

Product Name: LT-SW Series PIN Doide Switch
 Application: Wireless Communication

Material: Aluminum
 Temperature: -40~85°C
 Frequency Range: 0.02 To 3 GHz

• Color: Silver

Highlight: Absorptive SP6T PIN Diode Switch,
 PIN Diode Switch 3GHz, SP6T Switches

## **Product Description**

# 0.02 to 3 GHz LT-SW Series PIN Diode Switch

#### Quick Detail:

- · Aluminum Housing
- · Customizable Frequency
- · -40°C~+85°C Operating Temperature
- Fast Switching Time 100ns
  CE, RoHS, REACH compliant
- · 1 Year Warranty

## **Description:**


The LT-SW6TA-20M030S from ZR is a Absorptive PIN Diode Switch with Frequency 0.02 to 3 GHz, Isolation 60 dB, Switching Speed 250ns. Power Supply with bias +5V/240mA and -5V/50mA. More details for LT-SW6TA-20M030S can be seen below.

## Specifications:

Electrical / Optical Characteristics (Ta=25°C±3°C)

Items	Specification	Conditions
Part Number	LT-SW6TA-20M030S	
Туре	Absorptive	
Configuration	SP6T	
Frequency Range	0.02 to 3 GHz	
Insertion Loss	2.5 dB	
Isolation	60 dB	
Switching Speed	250 ns	
Control	TTL	
Input / Output VSWR	1.5:1	
Input Power	1.0 W	
Power Supply(Bias)	+5V / 240mA	
	-5V / 50mA	
Dimension	40*33.03*12mm	
Note: for custom specs, please contact us directly.		

## Outline Drawing (Unit: mm):



# ZRHITECH Sichuan ZR Hi-Tech Ltd.



13541202623



info@zrhitech.com



zrhitech.com