# 2 To 8 GHz SP3T Absorptive PIN Diode Switch

# **Basic Information**

Place of Origin: CHINABrand Name: ZR Hi-Tech

Model Number: LT-SW3TA-020080S

Minimum Order Quantity:

Packaging Details: carton packing
Delivery Time: 4 weeks
Payment Terms: T/T



# **Product Specification**

Product Name: LT-SW Series PIN Doide Switch Application: Wireless Communication

Material: Aluminum
Temperature: -40~85°C
Frequency Range: 2 To 8 GHz
Color: Silver

• Highlight: RF SP4T PIN Diode Switch,

 ${\bf PIN\ Diode\ Switch\ for\ Mobile\ Satellite},$ 

SP4T RF PIN Diode Switch

### **Product Description**

#### 2 to 8 GHz LT-SW Series PIN Diode Switch

#### Quick Detail:

- · Aluminum Housing
- · Customizable Frequency
- · -40°C~+85°C Operating Temperature
- · Fast Switching Time 100ns · CE, RoHS, REACH compliant
- · 1 Year Warranty

#### **Description:**


The LT-SW3TA-020080S from ZR is a Absorptive PIN Diode Switch with Frequency 2 to 8 GHz, Isolation 70 dB, Switching Speed 100ns. Power Supply with bias +5V/120mA and -5/50mA. More details for LT-SW3TA-020080S can be seen below.

#### Specifications:

Electrical / Optical Characteristics (Ta=25°C±3°C)

Items	Specification	Conditions
Part Number	LT-SW3TA-020080S	
Туре	Absorptive	
Configuration	SP3T	
Frequency Range	2 to 8 GHz	
Insertion Loss	1.8 dB	
Isolation	70 dB	
Switching Speed	100 ns	
Control	PIN	
Input / Output VSWR	1.5:1	
Input Power	1.0 W	
Power Supply(Bias)	+5V / 120mA	
	-5V / 50mA	
Dimension	40*25*10.5mm	
Note: for custom specs, please contact us directly.		

## Outline Drawing (Unit: mm):



# ZRHITECH Sichuan ZR Hi-Tech Ltd.



13541202623



info@zrhitech.com



zrhitech.com