2.0 to 4.0 GHz 30 Watt LT-PD Series 4-Way Power **Divider**

Basic Information

• Place of Origin: **CHINA** • Brand Name: ZR Hi-tech

LT-PD-4S-020040 Model Number:

Minimum Order Quantity:

Packaging Details: carton packing Delivery Time: 4 weeks Payment Terms: D/A,D/P,T/T



Product Specification

Highlight: 4.0 GHz Power Divider, 4 Way Power Divider

Product Description

2.0 to 4.0 GHz 4-Way Power Divider

Quick Detail:

- · 4-Way Power Divider
- · Stripline Design
- · -40°C~+70°C operating temperature
- · 2.0 to 4.0 GHz Frequency Range
- · Max Power 30 Watt
- · Insertion Loss < 0.6 dB
- · Isolation > 20 dB
- · CE, RoHS, REACH compliant
- · 1 Year Warranty

Description:

The LT-PD-4S-020040 from ZR is a 4-way power divider that operates from 2.0 to 4.0 GHz and can handle up to 30 Watt (CW) with 0.6 dB max insertion loss and 20 dB min isolation, The package interface uses SMA-Female connectors and is REACH and RoHS compliant. More details for LT-PD-4S-020040 can be seen below.

Specifications:

Electrical / Optical Characteristics (Ta=25°C±3°C)

Items	Specification	Conditions
Part Number	LT-PD-4S-020040	
Frequency Range	2.0 to 4.0 GHz	
Impedance	50 Ohms	
Input VSWR	1.3:1 Max.	
Output VSWR	1.2:1 Max.	
Insertion Loss	0.6 dB Max.	Excluding Nominal Splitter
		Loss 3.0dB
Isolation	20 dB Min.	
Amplitude Balance	0.6 dB Max.	
Phase Balance	6 Degrees Max.	
Input Power	30 kW	
Connectors	SMA-Female	
Dimension	56x43x10 mm	
Note: for custom spec	s, please contact us directl	у.

Outline Drawing (Unit: mm):









