2.0 to 4.0 GHz 30 Watt LT-PD Series 2-Way Power Divider

Basic Information

Place of Origin: CHINABrand Name: ZR Hi-tech

Model Number: LT-PD-2S-020040

Minimum Order Quantity:

Packaging Details: carton packing
Delivery Time: 4 weeks
Payment Terms: D/A,D/P,T/T



Product Specification

• Highlight: 2.0 to 4.0 GHz Power Divider

Product Description

2.0 to 4.0 GHz 2-Way Power Divider

Quick Detail:

- · 2-Way Power Divider
- · Stripline Design
- · -40°C~+70°C operating temperature
- · 2.0 to 4.0 GHz Frequency Range
- · Max Power 30 Watt
- · Insertion Loss < 0.35 dB
- \cdot Isolation > 20 dB
- · CE, RoHS, REACH compliant
- · 1 Year Warranty

Description:

The LT-PD-2S-020040 from ZR is a 2-way power divider that operates from 2.0 to 4.0 GHz and can handle up to 30 Watt (CW) with 0.35 dB max insertion loss and 20 dB min isolation, The package interface uses SMA-Female connectors and is REACH and RoHS compliant. More details for LT-PD-2S-020040 can be seen below.

Specifications:

Electrical / Optical Characteristics (Ta=25°C±3°C)

| Items | Specification | Conditions |
|-----------------------|------------------------------|----------------------------|
| Part Number | LT-PD-2S-020040 | |
| Frequency Range | 2.0 to 4.0 GHz | |
| Impedance | 50 Ohms | |
| Input VSWR | 1.25:1 Max. | |
| Output VSWR | 1.2:1 Max. | |
| Insertion Loss | 0.35 dB Max. | Excluding Nominal Splitter |
| | | Loss 3.0dB |
| Isolation | 20 dB Min. | |
| Amplitude Balance | 0.4 dB Max. | |
| Phase Balance | 4 Degrees Max. | |
| Input Power | 30 kW | |
| Connectors | SMA-Female | |
| Dimension | 28x28x10 mm | |
| Note: for custom spec | s, please contact us directl | y. |

Outline Drawing (Unit: mm):













