

TCXO

50~156.25MHz 9.2×14.2mm, High Precision & Low Phase noise TCXO

Quick Detail:

- Aluminum housing
- 3.3/5V VCC options
- -50°C~85°C operating temperature
- Small package
- High precision
- Low phase noise
- Optional three-state control function
- Anti-overload > 30000g
- CE, RoHS, REACH compliant
- 1 Year Warranty

Description:

The LT-CR-BT0914AZ is the newest addition to ZR's line of TCXOs. The standard part offers an ultra-tight stability of $\pm 0.28\text{ppm}$ to $\pm 2.0\text{ppm}$ over -50°C to +85°C across a supply voltage range of 3.3V/5.0V. The bt0914a-z uses a high refresh rate, or frequency calibration rate, to maintain a linear frequency output during temperature compensation. The 14.65 mm x 9.35 mm ceramic package and options for 1,000- or 3,000-piece reels make these components ideal for satellite communication, military communication equipment, base station, test and measurement equipment.

Specifications:

Electrical / Optical Characteristics (Ta=25°C±3°C)

Items	specification	Condition
Part Number	LT-CR-BT0914AZ	
Frequency Range	50MHz~156.25MHz	
Operating Voltage(VCC)	3.3V / 5V	
Operating Temperature	-50°C~+85°C	
Freq. Stability Vs. Temp.	$\pm 0.28\text{ppm}$ ~ $\pm 2.0\text{ppm}$	-40°C~+85°C @Height above 6mm

Frequency Tolerance	$\pm 0.5\text{ppm} \sim \pm 1.0\text{ppm}$	At shipment, nominal EFC, +25°C
Output Waveform	Sine Wave	
Voltage-control led voltage	1.5V $\pm 1.0\text{V}$	
Absolute Pull Range		
Phase Noise	<-145dBc@50~100MHz	@1kHz
	<-140dBc@50~100MHz@102.4~122.88MHz	
	<-135dBc@50~100MHz@102.4~122.88MHz@125~156.25MHz	
	<-130dBc@50~100MHz@102.4~122.88MHz@125~156.25MHz	
Overload Resistance		
Dimension	14.65 mm x 9.35 mm	

Outline Drawing (Unit: mm):

