

TCXO

**50~156.25MHz 25×25mm, Vibration Insensitive, High Precision & Low Phase noise
TCXO**

Quick Detail:

- Aluminum housing
- 3.3 / 5V VDD options
- -50°C~85°C operating temperature
- Small package
- High precision
- Low phase noise
- Optional three-state control function
- Anti-overload > 30000g
- CE, RoHS, REACH compliant
- 1 Year Warranty

Description:

The LT-CR-BT2525HZ is the newest addition to ZR's line of TCXOs. The standard part offers an ultra-tight stability of $\pm 0.5\text{ppm}$ to $\pm 2.0\text{ppm}$ over -50°C to +85°C across a supply voltage range of 3.3V / 5.0V. The bt2020h-z uses a high refresh rate, or frequency calibration rate, to maintain a linear frequency output during temperature compensation. The 25.4 mm x 25.4 mm ceramic package and options for 1,000- or 3,000-piece reels make these components ideal for satellite communication, military communication equipment, base station, test and measurement equipment.


Specifications:

Electrical / Optical Characteristics (Ta=25°C±3°C)

Items	specification	Condition
Part Number	LT-CR-BT2525HZ	
Frequency Range	50MHz~156.25MHz	
Operating Voltage(VDD)	3.3V / 5V	
Operating Temperature	-50°C~+85°C	
Freq. Stability Vs. Temp.	$\pm 0.5\text{ppm}$ ~ $\pm 2.0\text{ppm}$	-50°C~+85°C

Frequency Tolerance	$\pm 0.5\text{ppm} \sim \pm 1.5\text{ppm}$	At shipment, nominal EFC, +25°C
Output Waveform	Sine Wave	
Voltage-control led voltage	1.5V $\pm 1.0\text{V}$	
Absolute Pull Range		
Phase Noise	<-145dBc@50~100MHz	@1kHz
	<-140dBc@50~100MHz@102.4~122.88MHz	
	<-135dBc@50~100MHz@102.4~122.88MHz@125~156.25MHz	
	<-130dBc@50~100MHz@102.4~122.88MHz@125~156.25MHz	
Overload Resistance		
Dimension	25.4 mm x 25.4 mm	

Outline Drawing (Unit: mm):



Note:

Leave Pin 3 unconnected if Vcon is not used.
Leave Pin 4 unconnected if Vref is not used.

