

20 to 32 GHz LT-PA Series Power Amplifier

Quick Detail:

- Aluminum Housing
- Customizable Frequency
- -40 °C~+70 °C operating temperature
- Small Signal Gain 30dB
- Output Power 21dBm
- CE, RoHS, REACH compliant
- 1 Year Warranty

Description:

The LT-PA200320-G30P21 from ZR is a RF Amplifier with Frequency 20 to 32 GHz, Small Signal Gain 30 dB, Gain Flatness ± 3.0 dB, Output Power 21dBm, Input Power 5 dBm. Tags: Power Amplifier. More details for LT-PA200320-G30P21 can be seen below.

Specifications:

Electrical / Optical Characteristics (Ta=25 °C ± 3 °C)

Items	Specification	Conditions
Part Number	LT-PA200320-G30P21	
Configuration	Module with Connector	
Frequency Range	20 to 32 GHz	
Small Signal Gain	30 dB	
Gain Flatness	± 3.0 dB	
Output Power	21 dBm	
Input Power	5 dBm	
VSWR	2.0:1	
Power Supply	+12V / 500mA	
Operating Temperature	-40 to +70 °C	
Dimension	50*50*16 mm	
Note: for custom specs, please contact us directly.		

Outline Drawing (Unit: mm):

